



HELO-HSS and HST STEAM GENERATORS

All of these steam generators have stainless steel boilers with Incalloy 825 elements for long life and high out steam. The supply water to the unit is electronically controlled with timer, solenoid valve, and water level cut-out probes to protect the heating elements. Steam safety control is complete with built-in 25 minute electronic timer and safety pressure release valve.



Pressure Release Valve

HSS and HST

FEATURES

- A two color LED indicates if the generator is working or the temperature is reached
- Multifunction switch for light, ventilator, and essence pump
- Thermostat is adjustable from 20 C to 50C
- Chrome plated sensor with 5m cable
- 120 minutes timer
- Easy connection to the unit, low 12Vac
- Power : 230V or 400V 50HZ for HSS; 400V/50Hz for HST models.

| Helo Model | Voltage (50Hz) | Power (KW) | Room (M3) | Minimum Height |
|------------|----------------|------------|-----------|----------------|
| HSS34 | 230/400V | 3.4 | 1.5-2.5 | 190cm |
| HSS47 | 230/400V | 4.7 | 2.5-5 | 190cm |
| HSS60 | 230/400V | 6.0 | 5-7 | 190cm |
| HSS77 | 230/400V | 7.7 | 7-10 | 190cm |

| Helo Model | Voltage (50Hz) | Power (KW) | Room (M3) | Minimum Height |
|---|----------------|------------|-----------|----------------|
| HST90 | 400V | 9 | 10-12 | 190cm |
| HST120 | 400V | 12 | 12-15 | 190cm |
| HST140 | 400V | 14 | 15-18 | 190cm |
| Larger sizes are also available on request. | | | | |

Heavy or heat absorbing wall such as tiles, stone, and concrete requires a larger generator up to double the capacity shown in the table.


Available from:



Roma II Control



Midi Control



On/Off Control

PT.MONCOL GOLFUSA, Jakarta: Tel (021) 475-1127, Fax (021) 471-1972

Surabaya: Tel (031) 567-2474. Fax (0343) 859-107; Denpasar: Tel (0361) 281-082. Fax (0361) 288-805

